



## SEAL CONFIGURATIONS M4, M5 & M6






MOBILE M4, M5, M6




### M4 options:



### M5 options:



### M6 options:



## SPECIFICATIONS M4, M5 & M6

### STAINLESS STEEL COVER & FLAT WORKING SURFACE

	SEAL LENGTH			MAX. PRODUCT HEIGHT	USEFUL CHAMBER SIZE (WxDxH)	OUTSIDE DIMENSION (WxDxH)	STANDARD VOLTAGE*	POWER CONSUMPTION	WEIGHT
	L	S&S	L&S						
<b>M4</b>	620	2 x 520		200	max. 620 x 505 x 200 (L)	735 x 900 x 1130 (1470**)	400-3-50 Hz	3,3 kW	180 kg
<b>M5</b>	2 x 820	2 x 620	780 x 520	210	max. 805 x 605 x 200 (LS)	935 x 1000 x 1140 (1540**)	400-3-50 Hz	3,5 kW	240 kg
<b>M6</b>	2 x 1020	2 x 620	980 x 520	210	max. 1005 x 605 x 200 (LS)	1135 x 1000 x 1140 (1540**)	400-3-50 Hz	3,5 kW	280 kg

Dimensions in mm \*Machines can be supplied with all world wide voltages applicable \*\*Open cover requires more space

## OPTIONS M4, M5 & M6

	DIGITAL TIME CONTROL	SENSOR CONTROL	SEAL	SEAL CONFIGURATION	GAS	PUMP CAPACITY M <sup>3</sup>	CYCLE TIME
<b>M4</b>	10 programs	sensor/H <sub>2</sub> O	Double/CC/CCC/2S***	L S&S	gas	40 or 63 m <sup>3</sup>	20-40 sec
<b>M5</b>	10 programs	sensor/H <sub>2</sub> O	Double/CC/CCC/2S	L&L S&S L&S	gas	63 or 100 m <sup>3</sup>	25-35 sec
<b>M6**</b>	10 programs	sensor/H <sub>2</sub> O	Double/CC/CCC/2S	L&L S&S L&S	gas	100 m <sup>3</sup>	25-35 sec

\*\*Model M6 standard cover height 210 mm, optional cover 260 mm height \*\*\*CC = Clean Cut, CCC = Clean Cut Controlled, 2S = Two Sides