

## HENKOVAC TRAY SEALERS:

EASY AND QUICK MOULD CHANGE, EASY ACCESS,  
EASY TO CLEAN

*"Packaging of meat, vegetables, fruit, ready made meals portioned in practical trays with a professional presentation"*

The TPS 1000 and TPS 2000 are especially designed for easy and fast mould changes which consists off relatively light components. The transparent cover allows quick and full access for the mould change, loading and guiding the film and thorough cleaning of the machine. The TPS 2000 has 2 moulds which doubles the production capacity compared to the TPS 1000 or adds flexibility with the installation of 2 different moulds. This only requires changing the settings at the control panel for switching to a different tray dimension. The TPS range can be equipped with a special oxygen Busch pump for gasflush > 21% and photocell for centering printed film. The loading area can be extended, the exit belt can be motorized and the control unit has connections for auxiliary equipment.

TRAY SEALER TPS 2000



### SPECIFICATIONS TRAY SEALERS









|                 | MACHINE DIMENSION  | WORK HEIGHT | PUMP               | CYCLE TIME | VOLTAGE*     | POWER CONSUMPTION | AIR PRESSURE REQUIRED  | WEIGHT  |
|-----------------|--------------------|-------------|--------------------|------------|--------------|-------------------|------------------------|---------|
| <b>TPS 1000</b> | 4350 x 1180 x 1550 | 850         | 100 m <sup>3</sup> | 10-15 sec  | 400V-3-50Hz  | 6 kW              | 6 bar max. 400ltr/min. | 950 kg  |
| <b>TPS 2000</b> | 4750 x 1180 x 1550 | 850         | 160 m <sup>3</sup> | 10-15 sec  | 400V-3-50 Hz | 10 kW             | 6 bar max. 400ltr/min. | 1100 kg |

|                 | MAX DIMENSION TRAY | MAX HEIGHT TRAY | MAX WIDTH FILM | MAX DIAMETER FILM ROLL | CORE DIAMETER FILM ROLL |
|-----------------|--------------------|-----------------|----------------|------------------------|-------------------------|
| <b>TPS 1000</b> | 350 x 260          | 25 - 120        | 450            | 440                    | 76                      |
| <b>TPS 2000</b> | 2X 350 x 260       | 25 - 120        | 450            | 440                    | 76                      |

Dimensions in mm \*Machines can be supplied with all worldwide voltages applicable

### MAXIMUM TRAY DIMENSIONS

| MOULD CONFIGURATION TPS 1000 & TPS 2000 (LxDxH) |                 |   |
|---|-----------------|---|
| 1:1   | 350 x 260 x 120 |   |
| 1:2   | 150 x 260 x 120 |  |
| 1:3   | 120 x 260 x 120 |  |
| 1:4   | 90 x 260 x 120  |  |
| 1 x round                                       | Ø 260 x 120     |  |
| 2 x round                                       | Ø 150 x 120     |  |
| 3 x round                                       | Ø 120 x 120     |  |
| 4 x round                                       | Ø 90 x 120      |  |

Dimensions in mm

### OPTIONS TRAY SEALER

- > 100 m<sup>3</sup> Oxygen protected vacuum pump
- > Motorized exit belt
- > Additional loading area, per meter